



TLL46 SERIES

Opti-Brite LED Work Lights

- TLL46CFB – Raw lumen output: 2160 lm, Effective lumen output: 1492 lm
- TLL46TB – Raw lumen output: 2160 lm, Effective lumen output: 1346 lm
- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Low profile design – less than 2.5 inches deep
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10" lead and ground wire
- IP69K Rating: Highest designation available for water ingress testing, offering increased reliability and service life when subjected to severe environmental conditions or cleaning methods
- Available in bulk and polypack packaging
- **Lifetime LED Warranty**



Products

| Bulk | Polypack | Diodes | Description | Qty |
|----------|-----------|--------|---|-----|
| TLL46CFB | TLL46CFBP | 9 | Square LED work light, flood beam, 12-24V | 3 |
| TLL46TB | TLL46TBP | 9 | Square LED work light, trapezoid beam, 12-24V | 3 |

Accessories

| Bulk | Polypack | Diodes | Description | Qty |
|------|----------|--------|-------------|-----|
|------|----------|--------|-------------|-----|

Specifications

FMVSS:

MATERIALS: Polycarbonate lens, aluminum housing

VOLT/AMP: TLL46CFB: 12.8VDC - 1.65A, 24.0VDC - 1.0A
TLL46TB: 12.8VDC - 1.50A, 24.0VDC - 0.73A

WT/DIMS: TLL46CFB: 1.764 lbs. / 5" x 7" x 2.375"
TLL46TB: 1.764 lbs. / 5" x 7" x 2.375"

WARRANTY: Lifetime LED Warranty



AVAILABLE IN
PROTECTIVE

POLYPACK

